

Hagmans - Fasadfärg Titan

Product Description

Hagmans Facade Paint Titan is a self-cleaning and easy-to-apply facade paint that provides an extremely durable result and color stability. Specially developed for the Nordic climate with a unique hybrid combination of polyurethane alkyd and acrylic, the surface has superb flexibility, minimal water absorption and the highest dirt repellency.

Areas of use

The paint can be applied to new wood or wooden surfaces that have previously been painted with oil paint or acrylic. The paint gives a semi-gloss finish and is excellent for painting all types of wooden surfaces outdoors, such as facades, fences, carports and storage rooms.

Technical data:

Parameter	Value	Unit	Method
Area of application	Outdoor		
Binder	Acrylic / Polyurethane alkyd		
Completely dry	24-48 hours		
Dust dry	About 1 hour		
Re-paintable	After 2-4 hours		
Gloss	Semi-gloss		
Material consumption	6-10 m ² /L		
Temperature at painting	Minimum +5°C		
Thinner/Cleaning	Water		
Tools for painting	Brush, roller or paint sprayer		
VOC category	(Cat A/d): 130 g/l (2010)		
Volume Solids	36%	%	
Washability	Class 1 (EN 13300)		

Application Instructions

Before Painting

Always start by reading the instructions on the paint can and remember to be careful from the beginning. Good tools and careful preparation are the prerequisites for a successful painting result. Stir the paint well from the bottom before you start painting. Air and surface temperature are also important for the final result, do not paint if it is colder than +8°C. Check that the substrate is dry before painting, maximum 16% moisture content. Do not paint on sunny surfaces or if there is a risk of rain in the next 24 hours or dew within 1-2 hours after

painting has been completed. Old linseed oil/linseed oil paint can cause linseed oil blisters. The substrate must be clean, dry and firm.

Painting

Untreated wood that has been outdoors for more than 4 weeks should be washed and disinfected and loose wood fibers should be removed. Then prime the entire surface including end wood with 1 coat of Utegrund Kombi, this outdoor primer is a combination of primer and outdoor primer. Previously painted surfaces: wash with products intended for washing before painting and let dry well. In the event of fungal or algae infestation, the surface should be treated with Hagmans Algtvätt. Loose paint and loose wood fibers should be scraped/wire brushed away. Prime clean wood surfaces. Finish with two coats of Facade Paint Titan with the recommended drying time in between. Use a dense brush and work the paint well into the wood.

After Painting

Close the can tightly after use and store frost-free out of reach of children. Liquid paint residues should not be poured down the drain but left at the local waste disposal station.

Maintenance

For maintenance, use a soft scrub brush moistened with water and possibly Hagmans maintenance wash if necessary.

Informationen i detta dokument bygger på vår aktuella kunskap från laborietester och praktisk erfarenhet och kan ändras utan föregående meddelande; använd alltid senaste versionen. Produkten är endast avsedd för angivna användningsområden och, om tillämpligt, industriellt/yrkesmässigt bruk. Produkten är utformad och testad för att uppfylla gällande säkerhetskrav enligt produktansvarslagen. Användaren ansvarar för att produkten är lämplig för det specifika objektet och applikationssättet, samt att noggrant följa bruksanvisning, säkerhetsdatablad och gällande lagar. Underlåtenhet att följa detta sker på användarens egen risk.

Vi garanterar att produkten överensstämmer med våra specifikationer vid leveranstillfället. Vi ska under inga omständigheter ansvara för indirekta skador (såsom utebliven vinst, produktionsbortfall och andra följdskador) och vårt sammanlagda ansvar är begränsat till ersättning eller utbyte upp till fakturavärdet.

Vid osäkerhet om produktens lämplighet ska användaren kontakta oss innan användning. Vid reklamation ska dokumentation som styrker korrekt användning kunna uppvisas, annars kan reklamationen avslås.

För konsumentköp gäller konsumentköplagen och denna ansvarsfriskrivning begränsar inte konsumentens lagstadgade rättigheter.