

Hagmans - Fönsterfärg

Product Description

Hagmans Window Paint is a semi-gloss, high-quality window paint on an acrylate base, specially adapted to the very special requirements placed on a paint for painting wooden windows both outside and inside. A window paint must be able to withstand very high and low temperatures and also changes in humidity, and then have a constant climate on the other hand. The product is characterized by its very good resistance to UV radiation, which means that it retains its shine and color and provides a beautiful and maintenance-free surface for many years. It is also formulated to handle both the vertical and horizontal surfaces found on a window frame and also to paint over the sharp edges in a good way. It also provides a hard and resistant surface with low thermoplasticity.

Hagmans Window Paint is a semi-gloss, high-quality window paint on an acrylate base, specially adapted to the very special requirements placed on a paint for painting wooden windows both outside and inside. A window paint must be able to withstand very high and low temperatures and also changes in humidity, and then have a constant climate on the other hand. The product is characterized by its very good resistance to UV radiation, which means that it retains its shine and color and provides a beautiful and maintenance-free surface for many years. It is also formulated to handle both the vertical and horizontal surfaces found on a window frame and also to paint over the sharp edges in a good way. It also provides a hard and resistant surface with low thermoplasticity.

Areas of use

The product is suitable for both new wood that has been primed with Hagmans Utegrund Kombi or wooden surfaces that have previously been painted with oil paint. The product is suitable for both new wood that has been primed with Hagmans Utegrund Kombi or wooden surfaces that have previously been painted with oil paint.

Technical data:

Parameter	Value	Unit	Method
Area of application	Outdoor		
Binder	Acrylate		
Completely dry	48 hours		
Dust dry	2 hours		
Re-paintable	6-8 hours		
Gloss	Semi-gloss (35)		
Material consumption	6-8 m ² /L		
Temperature at painting	Min. +5°C		
Thinner/Cleaning	Water		
Tools for painting	Brush and spray (after thinning)		

Parameter	Value	Unit	Method
VOC category	(Cat. A/d): 130 g/l (2010)		
Volume Solids	40%	%	

Application Instructions

Before Painting

Always start by reading the instructions on the paint can and remember to be careful from the beginning. Good tools and careful preliminary work are the prerequisites for a successful painting result. Stir the paint well from the bottom before you start painting. Air and surface temperature are also important for the final result, do not paint if it is colder than +5°C. The substrate must be clean, dry and solid. Check that the substrate is sufficiently dry before painting, maximum 16% moisture content. Do not paint on sunny surfaces or if there is a risk of rain in the next 24 hours or dew within 1-2 hours after painting has been completed. Old linseed oil/linseed oil paint can cause linseed oil blisters. Untreated wood that has been outdoors for more than 4 weeks must be washed and disinfected and loose gray wood fibers must be removed. Then prime with Hagmans Utegrund Kombi. Previously painted surfaces must be washed with products intended for washing before painting and then allowed to dry well. In the event of fungal and algae infestation, the surface should be treated with Hagmans Algtvätt. Loose paint and loose wood fibers should be scraped/wire brushed away. Prime clean wood surfaces.

Painting

Hagmans Window Paint is applied with a suitable brush and worked well into the substrate. Be careful not to paint too thickly, rather 2 thin layers than one thick one, and to work the paint well into the surface. The paint can also be rolled but must then be reworked with a brush. This also applies when spraying, in which case the paint is also diluted with 5-10% water. Wait to close the window completely until the paint is completely dry. A tip is to place a match between the sash and frame for the first few days.

After Painting

Dry the tools thoroughly before cleaning in water. Close the can tightly after use and store out of reach of children. Liquid paint residues should not be poured down the drain but left at the local environmental station.

Maintenance

Use Hagmans Maintenance Wash to clean the surface. Never use alcohol when cleaning paint or varnish.

Informationen i detta dokument bygger på vår aktuella kunskap från laboratorietester och praktisk erfarenhet och kan ändras utan föregående meddelande; använd alltid senaste versionen. Produkten är endast avsedd för angivna användningsområden och, om tillämpligt, industriellt/yrkesmässigt bruk. Produkten är utformad och testad för att uppfylla gällande säkerhetskrav enligt produktansvarslagen. Användaren ansvarar för att produkten är lämplig för det specifika objektet och applikationssättet, samt att noggrant följa bruksanvisning, säkerhetsdatablad och gällande lagar. Underlåtenhet att följa detta sker på användarens egen risk.

Vi garanterar att produkten överensstämmer med våra specifikationer vid leveranstillfället. Vi ska under inga omständigheter ansvara för indirekta skador (såsom utebliven vinst, produktionsbortfall och andra följdskador) och vårt sammanlagda ansvar är begränsat till ersättning eller utbyte upp till fakturavärdet.

Vid osäkerhet om produktens lämplighet ska användaren kontakta oss innan användning. Vid reklamation ska dokumentation som styrker korrekt användning kunna uppvisas, annars kan reklamationen avslås.

För konsumentköp gäller konsumentköplagen och denna ansvarsfriskrivning begränsar inte konsumentens lagstadgade rättigheter.